

LPG

STEEL PORTABLE



SPECIFICATIONS

STANDARD

MODEL/SIZE (LBS)	4.25	11	20	30	40	43.5	60*	100*
HEIGHT (IN)	11.8	16.6	17.2	23.7	29.3	32.5	44.1	48
LPG CAPACITY (GAL)	1	2.6	4.7	7.1	9.4	10.3	14.2	23.6
WATER CAPACITY (LBS)	12	26.2	47.6	71.5	95.2	103.6	143	239
NOMINAL TARE WEIGHT (LBS)	11	13.3	17.0	23.3	28.7	33.9	48.1	68
CYLINDER DIAMETER (IN)	9.1	9.1	12.3	12.3	12.3	12.3	12	14.7
CYLINDER VOLUME (CU. IN)	332	725	1,318	1,980	2,635	2,868	3,955	6,616
COLLAR DIAMETER (IN)	6.5	6.5	6.5	6.5	6.5	6.5	6.5	6.5
COLLAR HEIGHT (IN)	4	4	4	4	4	5.1	5.1	5.1
FOOTRING DIAMETER (IN)	9.1	7.8	7.8	7.8	7.8	12	12	14.5
HORIZONTAL DESIGN	-	-	Available	Available	Available	-	-	-
VALVE	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
STANDARD SPECIFICATION	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BW260	DOT-4BW240

METRIC

MODEL/SIZE (LBS)	4.25	11	20	30	40	43.5	60*	100*
HEIGHT (MM)	300	427	450	602	744	825.5	1,120	1,219
LPG CAPACITY (L)	3.8	9.8	17.3	26.9	35.6	39	53.8	86.7
WATER CAPACITY (KG)	5.4	11.9	21.6	32.4	42.2	47	65	108.4
NOMINAL TARE WEIGHT (KG)	5	6.0	7.7	10.5	13.0	15.4	21.8	30.8
CYLINDER DIAMETER (MM)	231	231	312	312	312	312	305	373
CYLINDER VOLUME (L)	5.4	11.9	21.6	32.4	42.2	47	65	108.4
COLLAR DIAMETER (MM)	165	165	165	165	165	165	165	165
COLLAR HEIGHT (MM)	102	102	102	102	102	130	130	130
FOOTRING DIAMETER (MM)	231	198	198	198	198	305	305	368
HORIZONTAL DESIGN	-	-	Available	Available	Available	-	-	-
VALVE	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-510 NO OPD	CGA-510 NO OPD	CGA-510 NO OPD
STANDARD SPECIFICATION	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BA240	DOT-4BW260	DOT-4BW240

All dimensions are approximate.

*Available with cap and flange

200 OLD WILSON BRIDGE ROAD
COLUMBUS, OHIO 43085
P: 614.438.3013
F: 614.438.3083

TOLL-FREE: 866.928.2657
CUSTOMERSERVICE@WORTHINGTONINDUSTRIES.COM
WORTHINGTONINDUSTRIES.COM



LPG

ALUMINUM PORTABLE



SPECIFICATIONS

STANDARD

MODEL/SIZE (LBS)	6	10	20	30	40
HEIGHT (IN)	22.5	15.9	20.2	25.9	32.1
LPG CAPACITY (GAL)	1.4	2.4	4.7	7.1	9.4
WATER CAPACITY (LBS)	15	23.8	47.6	71.5	95.2
NOMINAL TARE WEIGHT (LBS)	8.1	9.7	13.0	16.5	19.5
CYLINDER DIAMETER (IN)	6.3	10.3	12.3	12.3	12.3
CYLINDER VOLUME (CU. IN)	415	664	1,318	1,999	2,635
COLLAR DIAMETER (IN)	5.7	7.9	7.9	7.9	7.9
COLLAR HEIGHT (IN)	6.5	5.5	5.5	5.5	5.5
FOOTRING DIAMETER (IN)	6.2	8	8	8	8
HORIZONTAL DESIGN	-	Available	Available	Available	Available
VALVE	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD
STANDARD SPECIFICATION	DOT-4E260	DOT-4E240	DOT-4E240	DOT-4E240	DOT-4E240

METRIC

MODEL/SIZE (LBS)	6	10	20	30	40
HEIGHT (MM)	571	404	513	658	814
LPG CAPACITY (L)	5.4	9.1	17.3	26.9	35.6
WATER CAPACITY (KG)	6.8	10.8	21.6	32.4	43.2
NOMINAL TARE WEIGHT (KG)	3.7	4.4	5.9	7.5	8.8
CYLINDER DIAMETER (MM)	160	261	312	312	312
CYLINDER VOLUME (L)	6.8	10.8	21.6	32.7	43.5
COLLAR DIAMETER (MM)	144.8	200	200	200	200
COLLAR HEIGHT (MM)	165	140	140	140	140
FOOTRING DIAMETER (MM)	158	203	203	203	203
HORIZONTAL DESIGN	-	Available	Available	Available	Available
VALVE	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD	CGA-791 w/OPD
STANDARD SPECIFICATION	DOT-4E260	DOT-4E240	DOT-4E240	DOT-4E240	DOT-4E240

All dimensions are approximate.

200 OLD WILSON BRIDGE ROAD
COLUMBUS, OHIO 43085
P: 614.438.3013
F: 614.438.3083

TOLL-FREE: 866.928.2657
CUSTOMERSERVICE@WORTHINGTONINDUSTRIES.COM
WORTHINGTONINDUSTRIES.COM

